




Torque wrench

Nm min-max: 60 – 320 Nm · Tolerance: 4 % · Square, solid 12.5 mm (1/2 inch)

Article no.: 5123-2CLT
EAN: 4000896104222

Product information

- Click-Lens-Type with value readout in the display guarantees security for the user
- **Accuracy $\pm 4\%$ of the scale value** (in direction of actuation for right-hand tightening
For left-hand tightening, use our torque wrenches with insert tool)
- Safety:
 - Haptic (close-gap release)
 - Audible (“click” sound)
- Reversible ratchet
- Easy and safe adjustment of the desired torque value by turning the handle
- Knob for additionally locking the set value
- Three large digits for an easy-to-read torque setting
- With calibration certificate and serial number
- Secure storage in safe box with display window
- Surface: hard chrome plated
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: Square, solid 12.5 mm (1/2 inch)
- Dimensions / length: 660 mm
- Net weight: 1.53 kg
- Nm min-max: 60 – 320 Nm
- Tolerance: 4 %
- Scale Graduation (Nm): 2 Nm
- Actuating force min.-max. kg: 10.8 – 59.4 kg
- Number of teeth: 32 (Opening angle 11.25°)
- Head Thickness a: 19.6 mm
- Head Width b: 44 mm
- **Service-friendly** (do-it-yourself repair sets for ratchets)
- No risk of losing the square like there is with the wrench
- **Hard chrome-plated** steel tube - **slim**, but very sturdy and wear-resistant
- Integrated shift lever with free-running function on  model **reducing the risk of injury and malfunction**
- Ergonomically shaped handle with collar **reduces the risk of slipping-off and injury**
- Safety locking of the handle – no risk of injury!
- Safe and exact adjustment of the desired release torque.
Optimal and easy reading of the torque value
- Large convex display (replaceable) optimises the readability
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required





TECHNICAL DATA

- **Output:** 12⁵ 1/2
- **Head width b:** 44 mm
- **Torque min Nm:** 60 Nm
- **Tightening torque max.:** 320 Nm
- **Scale graduation (Nm):** 2 Nm
- **Tolerance:** 4 %
- **Standard:** DIN 3120, DIN EN ISO 6789-2:2017, ISO 1174-1
- **Surface:** hard chrome plated
- **Dimensions / length:** 660 mm
- **Number of teeth:** 32 teeth
- **Operating angle:** 11.25 °
- **Length_min-max:** 19.6 mm

