



Torque wrench

Nm min-max: 1 – 6 Nm · Tolerance: 4 % · Square, solid 6.3 mm (1/4 inch)

Article no.: 6106-1CT

EAN: 4000896173167

Product information

- Safety:
 - Haptic (close-gap release)
 - Audible (“click” sound)
- Easy and safe adjustment of the desired torque value by turning the handle
- Especially slim design thanks to spring-loaded puller sleeve for locking the setting values
- **Accuracy $\pm 2\%$ of the scale value** (in direction of actuation for right-hand tightening
For left-hand tightening, use our torque wrenches with insert tool)
6106-1 CT: $\pm 4\%$ accuracy of the scale value
- Application: engines, gearboxes, machinery, industry, model making
- With calibration certificate and serial number
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: Square, solid 6.3 mm (1/4 inch)
- Dimensions / length: 197 mm
- Net weight: 0.3 kg
- Nm min-max: 1 – 6 Nm
- Tolerance: 4 %
- Scale Graduation (Nm): 0.1 Nm
- Actuating force min.-max. kg: 0.7 – 4.4 kg
- Number of teeth: 20 (Opening angle 18°)
- Head Thickness a: 10.2 mm
- Head Width b: 24 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required



TECHNICAL DATA

- **Output:** $6.3^{1/4}$
- **Head width b:** 24 mm
- **Torque min Nm:** 1 Nm
- **Tightening torque max.:** 6 Nm
- **Scale graduation (Nm):** 0.1 Nm
- **Tolerance:** 4 %
- **Signal transmitter:** false
- **Standard:** DIN 3120, DIN EN ISO 6789-2:2017, ISO 1174-1
- **Dimensions / length:** 197 mm
- **Number of teeth:** 20 teeth
- **Operating angle:** 18 °
- **Length_min-max:** 10.2 mm

