



## Torque wrench

Nm min-max: 2 – 10 Nm · Tolerance: 2 % · Square, solid 6.3 mm (1/4 inch)

**Article no.:** 6108-1CT  
**EAN:** 4000896062218

### Product information

- Safety:
  - Haptic (close-gap release)
  - Audible (“click” sound)
- Easy and safe adjustment of the desired torque value by turning the handle
- Especially slim design thanks to spring-loaded puller sleeve for locking the setting values
- **Accuracy  $\pm 2\%$  of the scale value** (in direction of actuation for right-hand tightening  
For left-hand tightening, use our torque wrenches with insert tool)  
6106-1 CT:  $\pm 4\%$  accuracy of the scale value
- Application: engines, gearboxes, machinery, industry, model making
- With calibration certificate and serial number
- DIN EN ISO 6789-2:2017, DIN 3120, ISO 1174-1
- Made in Germany
- Output: Square, solid 6.3 mm (1/4 inch)
- Dimensions / length: 198 mm
- Net weight: 0.34 kg
- Nm min-max: 2 – 10 Nm
- Tolerance: 2 %
- Scale Graduation (Nm): 0.2 Nm
- Actuating force min.-max. kg: 1.4 – 7.3 kg
- Number of teeth: 20 (Opening angle 18°)
- Head Thickness a: 10.2 mm
- Head Width b: 24 mm
- **No more turning back:** Continuous long-term tests on the 5000 series and 6000 series of HAZET torque wrenches have demonstrated that turning them back to the smallest scale value is not required



# TECHNICAL DATA

- **Output:**  $6.3^{1/4}$
- **Head width b:** 24 mm
- **Torque min Nm:** 2 Nm
- **Tightening torque max.:** 10 Nm
- **Scale graduation (Nm):** 0.2 Nm
- **Tolerance:** 2 %
- **Signal transmitter:** false
- **Standard:** DIN 3120, DIN EN ISO 6789-2:2017, ISO 1174-1
- **Dimensions / length:** 198 mm
- **Number of teeth:** 20 teeth
- **Operating angle:** 18 °
- **Length\_min-max:** 10.2 mm

