

The basic core drill range for professional use. Fully ground core drill made from high-performance high-speed steel on CNC-controlled grinding centres, with good discharge of chips. Drilling with minimal effort. For working on a horizontal plane, BDS recommends the BDS 5200 high-performance lubrication spray.

HSS-Standard short core drill

- > 30 mm cutting depth
- > 19 mm Weldon shank ($\frac{3}{4}$ "



HSS-Standard long core drill

- > 55 mm cutting depth
- > 19 mm Weldon shank ($\frac{3}{4}$ "



HSS-STANDARD SERIES			
Ø mm	ORDER NO.	Ø mm	ORDER NO.
12	KBK 012	36	KBK 036
13	KBK 013	37	KBK 037
14	KBK 014	38	KBK 038
15	KBK 015	39	KBK 039
16	KBK 016	40	KBK 040
17	KBK 017	41	KBK 041
17.5	KBK 175	42	KBK 042
18	KBK 018	43	KBK 043
19	KBK 019	44	KBK 044
19.5	KBK 195	45	KBK 045
20	KBK 020	46	KBK 046
21	KBK 021	47	KBK 047
22	KBK 022	48	KBK 048
23	KBK 023	49	KBK 049
24	KBK 024	50	KBK 050
25	KBK 025	51	KBK 051
26	KBK 026	52	KBK 052
27	KBK 027	53	KBK 053
28	KBK 028	54	KBK 054
29	KBK 029	55	KBK 055
30	KBK 030	56	KBK 056
31	KBK 031	57	KBK 057
32	KBK 032	58	KBK 058
33	KBK 033	59	KBK 059
34	KBK 034	60	KBK 060
35	KBK 035		

HSS-STANDARD SERIES			
Ø mm	ORDER NO.	Ø mm	ORDER NO.
12	KBL 012	36	KBL 036
13	KBL 013	37	KBL 037
14	KBL 014	38	KBL 038
15	KBL 015	39	KBL 039
16	KBL 016	40	KBL 040
17	KBL 017	41	KBL 041
17.5	KBL 175	42	KBL 042
18	KBL 018	43	KBL 043
19	KBL 019	44	KBL 044
19.5	KBL 195	45	KBL 045
20	KBL 020	46	KBL 046
21	KBL 021	47	KBL 047
22	KBL 022	48	KBL 048
23	KBL 023	49	KBL 049
24	KBL 024	50	KBL 050
25	KBL 025	51	KBL 051
26	KBL 026	52	KBL 052
27	KBL 027	53	KBL 053
28	KBL 028	54	KBL 054
29	KBL 029	55	KBL 055
30	KBL 030	56	KBL 056
31	KBL 031	57	KBL 057
32	KBL 032	58	KBL 058
33	KBL 033	59	KBL 059
34	KBL 034	60	KBL 060
35	KBL 035		

EJECTOR PIN FOR KBK, Ø 12 – 60 mm	
ORDER NO.	
ZAK 075	

EJECTOR PIN FOR KBL, Ø 12 – 60 mm	
ORDER NO.	
ZAK 100	