





# Cable Cutter

- For cutting copper and aluminium cable with strong rubber or plastic sheathing
- Ratchet-shaped clamping of the cable ensures crimp-free cutting
- Not suitable for steel wire, aluminium alloys and hard-drawn copper conductors
- Special cutting geometry and precision cutting for a clean cut without any burrs
- Opening of the blade in each position possible
- Optimum leverage, easy handling and minimum effort by ratchet action
- Made of special steel, high-strength parts that are especially subject to wear and tear are additionally hardened and tempered

SKU: 046-250

Art-Nr.: 046E-250
Spare Swivel
Knife



## Safety Notes



Use tools for indicated purposes only.

Before using the cutting tools please wear body protection such as safety mask, safety glasses and hand protection.

Beware of wire ends flying off!

#### General Information

#### Cable Cutter

An optimum geometrical cutting shape now makes crimp-free cutting possible by means of plastic tubes and hoses. But not only the shape of the cut makes this possible; the ideal transfer of muscle power to the cutter is a major factor.



#### Connecting to the future

Solar energy is a clean alternative source of electricity. To make sure it is also a safe source, junction box and switch cabinet wiring has to be properly stripped, crimped and connected up. Using NWS wire stripping and crimping tools, electricians can handle wires and cables in line with all the applicable regulations and down to the millimetre. In this way, whether private houses, factory roofs or photovoltaic installations, they all become clean and safe players in the transition to renewable energy sources.



## Downloads



046-250.jpg



detail\_046-250\_1 102220952.jpg

# Technical Data

| 4 >        | Length - mm  | 250              |
|------------|--|------------------|
| 4 F        | Length - in  | 9 3/4            |
| <b>©</b>   | Cable - Al + Cu multi-wired conductor single and stranded conductor - cutting capacity - Ø mm            | 32               |
| <b>9</b> ° | Cable - Al + Cu multi-wired conductor single and stranded conductor - cutting capacity - mm <sup>2</sup> | 300              |
| -          | With opening spring  | 8                |
| 2,7        | Weight - g   | 670              |
| 9          | Packing unit   | 1                |
| Ш          | Barcode  | 40 03758 04601 2 |