

Chain Nose Pliers (Radio Pliers), angled 45°

- | For cutting hard and soft wires
- | For holding, gripping, bending and cutting work
- | Cutting edges inductively hardened
- | With cutting edge and burner hole
- | With long, 45°-angled, flat-round jaws
- | Serrated inside jaws
- | Integrated ring spanner
- | Handles with ergonomically shaped SoftGripp multi-component sleeves
- | SoftGripp handles with SystemSocket for holding optionally available accessories, e.g. the easily attached SystemClip for fall protection
- | Made of tool steel, forged, oil-hardened

SKU: 141-69-170

Related Products

 <p>Art-Nr.: 819-1 System Clip with Lanyard</p>	 <p>Art-Nr.: 819-2 System Clip with Opening Spring, Size 1+2</p>	 <p>Art-Nr.: 819-3 System Clip with Opening Spring, Size 3+4</p>
 <p>Art-Nr.: 819-4 E-Detector</p>	 <p>Art-Nr.: 820-12 Tool Tethering System</p>	

Safety Notes



Use tools for indicated purposes only.

Before using the cutting tools please wear body protection such as safety mask, safety glasses and hand protection.

Beware of wire ends flying off!

General Information


Finish 69

Our pliers, cutters & wrenches with the attractive titanium finish are supplied with our new SoftGripp 3K sleeves. The triple zone sleeves provide a firm grip which is pleasant to the touch, thanks to ergonomically designed handles. The pliers, cutters & wrenches themselves are drop-forged tool steel, special tool steel or chrome vanadium steel and are oil hardened. The cutting edges of all these cutting tools are induction- hardened to ensure they are able to cope with the needs of professionals in industry and the trades.



Keeping a grip on the matter in hand




Assembly jobs in high places offer not only excellent views but also serious challenges. Here, where freedom of movement is restricted, every move the worker makes must make sense and the safety of the workers, machines and tools must have priority. NWS industrial tools enable workers to keep a grip on things. Their ergonomic design reduces work effort, when working overhead, for example. With the tools secured with the SystemClip, they are guaranteed not to fall if dropped, which makes work safer and easier.



SoftGripp with SystemSocket









When we developed our handle sleeves, the focus was on functionality, safety and environmental compatibility. The SoftGripp sleeves provide firm but comfortable grip as you work thanks to the triple-component texture. The tailored shape of the handles and the combination of different, environmentally compatible materials makes the tool rest more snugly in the hand. The ergonomically designed SoftGripp, with its multi-zone blend of handle textures, coupled with the optional spring-loaded opening mechanism, ensure strain-free working. To ensure maximum safety, the tools feature an optimised shape to prevent hands slipping off the tool and the SystemClip, which secures the tools when working on a roof, scaffolding or construction site. The SystemClip, which is easily attached on the SystemSocket, creates a quick, secure connection between the tool and the strap and features an integrated pocket for storing the opener spring.

Downloads

	141-69-205.jpg		detail_SystemSocket 49_69.jpg		detail_819-1_130 7121734.jpg
---	----------------	---	-------------------------------	---	------------------------------

Technical Data

141-69-170		
↔	Length - mm	170
↔	Length - in	6 3/4
□	Jaw shape	⊙
✂	Cutting edge shape	✂
⦿	Soft wire (220 N/mm ²) copper, aluminium, plastic - cutting capacity - Ø mm	2,5
●	Medium hard wire (750 N / mm ²) nail, wire nail - cutting capacity - Ø mm	1,6

	Hard wire (1800 N / mm ²) wire rope fiber, steel rope - cutting capacity - Ø mm	-
	Angle of the tool head	45°
	Wrench size - mm	15
	DIN standards - National, European and worldwide	DIN ISO 5745
	Cutting edge hardness - HRC	57 - 59
	Weight - g	145
	Packing unit	6
	Barcode	40 03758 14117 5