

Whitworth pipe thread G, DIN-ISO 228							800	800	Ms	INOX			
Material groups							P M K N S H	P M K N S H	P M K N S H	P M K N S H			
Execution								LH		SPN			
Quality of material							HSS	HSS	HSS	HSSE			
Chamfer							1,75P	1,75P	1,25P	2,25P			
G	Ød,	1"/P	P	ØD x E	W		DIN-EN 24231				INDEX		
							Norm	Tol.					
G1/8	9,73	28	0,907	30 x 11	4	9,62	3123	●	○	●	●		
G1/4	13,16	19	1,337	38 x 10	4	13,03	3127	●	●	●	●		
G3/8	16,66	19	1,337	45 x 14	5	16,54	3129	●	●	●	●		
G1/2	20,96	14	1,814	45 x 14	6	20,81	3131	●	●	●	●		
G5/8	22,91	14	1,814	55 x 16	5	22,77	3133	●	○	○	○		
G3/4	26,44	14	1,814	55 x 16	6	26,30	3135	●	●	●	●		
G7/8	30,20	14	1,814	65 x 18	6	30,06	3137	●	○	○	○		
G1	33,25	11	2,309	65 x 18	7	33,07	3139	●	●	●	●		
G1.1/8	37,90	11	2,309	75 x 20	7	37,72	3141	○	○	○	○		
G1.1/4	41,91	11	2,309	75 x 20	8	41,73	3143	●	○	○	○		
G1.3/8	44,32	11	2,309	90 x 22	7	44,14	3145	○	○	○	○		
G1.1/2	47,80	11	2,309	90 x 22	7	47,62	3147	●	○	○	○		
G1.3/4	53,75	11	2,309	105 x 22	8	53,57	3151	○	○	○	○		
G2	59,61	11	2,309	105 x 22	8	59,43	3155	○	○	○	○		
G2.1/4	65,71	11	2,309	120 x 22	8	65,49	3157	○	○	○	○		

