

American unified coarse thread UNC, ANSI B-1.1								800				
Material groups												
Execution												
Quality of material								HSS				
Chamfer								1,75P				
UNC	Ød <sub>1</sub>	1"/P	P	ØD x E	W		Norm		DIN-EN 22 568			
							Tol.	INDEX	2A			
									N1-121001			
No 5 - 40	3,175	40	0,635	20 x 5	3	3,09	4105		●			
No 6 - 32	3,505	32	0,794	20 x 5	3	3,41	4106		●			
No 8 - 32	4,166	32	0,794	20 x 7	3	4,07	4108		●			
No 10 - 24	4,826	24	1,058	20 x 7	3	4,71	4110		●			
No 12 - 24	5,486	24	1,058	20 x 7	4	5,37	4112		●			
1/4 - 20	6,35	20	1,270	20 x 7	4	6,22	4127		●			
5/16 - 18	7,938	18	1,411	25 x 9	4	7,80	4128		●			
3/8 - 16	9,525	16	1,588	30 x 11	4	9,37	4129		●			
7/16 - 14	11,112	14	1,814	30 x 11	4	10,95	4130		●			
1/2 - 13	12,7	13	1,954	38 x 14	4	12,52	4131		●			
9/16 - 12	14,288	12	2,117	38 x 14	4	14,10	4132		●			
5/8 - 11	15,875	11	2,309	45 x 18	5	15,68	4133		●			
3/4 - 10	19,05	10	2,540	45 x 18	5	18,84	4135		●			
7/8 - 9	22,225	9	2,822	55 x 22	5	22,00	4137		●			
1 - 8	25,4	8	3,175	55 x 22	5	25,16	4139		●			
1.1/8 - 7	28,575	7	3,629	65 x 25	5	28,31	4141		○			
1.1/4 - 7	31,75	7	3,629	65 x 25	6	31,49	4143		○			
1.3/8 - 6	34,925	6	4,233	65 x 25	7	34,63	4145		○			
1.1/2 - 6	38,1	6	4,233	75 x 30	6	37,80	4147		○			
1.3/4 - 5	44,45	5	5,080	90 x 36	6	44,12	4151		○			
2 - 4.1/2	50,8	4.1/2	5,645	90 x 36	7	50,45	4155		○			

5

